

VARIABLE FORCE

20 - 40 RANGE

STANDARD AND STAINLESS STEEL



Standard features:



Optional features:



VARIABLE FORCE

Custom sizes available on request

CODE	STRUT REFERENCE	STROKE (S)	EXTENDED LENGTH (EL)
STEEL NS-V	20 - 100	100	311
	20 - 150	150	411
	20 - 200	200	511
	20 - 250	250	611
	20 - 300	300	711
STAINLESS NS-SS-V	20 - 350	350	811
	20 - 400	400	911
	20 - 450	450	1011
	20 - 500	500	1111
	20 - 600	600	1311
	20 - 700	700	1511
	20 - 800	800	1711

STANDARD RANGE SPECIFICATION (NS-V)

FORCE RANGE: (specify when ordering)	300 - 5000N
PANEL WEIGHT: (per pair of struts)	300 - 500kg
FORCE PROGRESSION:	45%
WORKING TEMPERATURE RANGE:	-30°C to +80°C
MATERIAL:	STEEL
ROD:	QPP
BODY COATING:	POWDER COATING
GUARANTEE:	2 YEARS

Supplied at maximum force unless specified otherwise

STAINLESS STEEL VARIANT (NS-SS-V)

ROD:	CHROME PLATED 316
BODY:	316 SS (STAINLESS STEEL)

Please add 5mm to the body length for the stainless steel variant



Please call for details on longer stroke sizes

BRACKETS

See pages 58 - 66 for our full range

END FITTINGS

See pages 53 - 57 for our full range

CODE	STEEL	PLASTIC	SS (STAINLESS STEEL)
BALL JOINTS	B16	-	-
EYE ENDS	E14	-	-
CLEVIS FORKS	C4	-	-



Distributed & Supported Worldwide

VERSION 19.10